

**2002**

**Virginia Department of Transportation  
Daily Traffic Volume Estimates  
Including Vehicle Classification Estimates**

where available

**Special Locality Report**

**173**

Town of Boydton

Prepared By

**Virginia Department of Transportation  
Mobility Management Division**

In Cooperation With

**U.S. Department of Transportation  
Federal Highway Administration**

Virginia Department of Transportation  
Mobility Management Division  
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people at VDOT Mobility Management's Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

## **Publication Notes**

### **Parallel Roads**

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a “Combined Traffic Estimates for Parallel Roadways on this Route” or “Combined Traffic” identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate “NA” for not available.

---

VDOT’s traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating “NA” for not available. It is the intention of the VDOT’s Mobility Management Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate “NA” for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

**Route:** The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

**Length:** Length of the traffic segment in miles.

**AADT:** Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

**QA:** Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

**4Tire:** Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

**Bus:** Percentage of the traffic volume made up of busses.

**2Axle Truck:** Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

**3+Axle Truck:** Percentage of the traffic volume made up of single unit trucks with three or more axles.

**1Trail Truck:** Percentage of the traffic volume made up of units with a single trailer.

**2Trail Truck:** Percentage of the traffic volume made up of units with more than one trailer.

**QC:** Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

**Peak Hour:** The estimate of the traffic volume for the 30<sup>th</sup> highest traffic volume occurring in a one-year period divided by the AADT for the same one-year period.

**QK:** Quality of the Peak Hour estimate:

- A Factor based on 30th Highest Hour Observed During 12 Months of Continuous Traffic Data
- B Factor based on 30th Highest Hour Observed During Less than 12 Months of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of 30th Highest Hour
- N Peak Hour Factor of Similar Neighboring Traffic Link
- O Provided by External Source

**Dir Factor:** The estimate of the portion of the traffic volume traveling in the peak direction during the Peak Hour..

**AAWDT:** Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

**QW:** Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

**Year:** Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

# Route Shield Legend

## Route Systems



Interstate Route

Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.



US Route



Virginia State Route



Secondary Route

## Special Routes



Bus - Business Route

Bypas - Bypass Route

Truck - Truck Route



ALT - Alternate Route

Wve - Wve Route connector



P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.



The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation  
 Mobility Management Division  
 2002  
 Annual Average Daily Traffic Volume Estimates By Section of Route  
 Town of Boydton

Route	Length	AADT	QA	4Tire	Bus	Truck				QC	Peak Hour	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
<b>Town of Boydton</b>																
58	0.60	4100	N	83%	1%	WCL Boydton				N	0.105	N	0.549	4100	N	2002
						NCL Boydton										
Bus 58	0.48	1700	G	96%	1%	US 58 West of Boydton				F	0.103	F	0.56	1700	G	2002
						SR 92										
Bus 58	0.55	1200	G	96%	1%	2%	0%	1%	0%	F	0.123	F	0.632	1200	G	2002
						NCL Boydton										
92	0.32	1200	G	97%	0%	1%	0%	1%	0%	F	0.102	F	0.694	1200	G	2002
						US 58 Bus										
						NCL Boydton										
688	0.15	1000	G	92%	3%	2%	0%	3%	0%	F	0.103	F	0.512	1000	G	2002
						WCL BOYDTON										
707	0.31	1100	G	94%	2%	2%	0%	2%	0%	C	0.096	F	0.608	1100	G	2002
						SCL BOYDTON										
707	0.13	1300	G	94%	2%	2%	0%	2%	0%	F	0.088	F	0.578	1300	G	2002
						58-1205										
						US 58 BUS; SR 92										
756	0.37	820	G	96%	1%	2%	0%	0%	0%	C	0.089	F	0.513	820	G	2002
						SCL BOYDTON										
756	0.29	580	G	96%	1%	2%	0%	0%	0%	F	0.087	F	0.558	580	G	2002
						58-1201										
756	0.12	200	R			58-707				NA			NA			08/16/2001
						58-1213										
1201	0.06	410	G	98%	0%	1%	0%	0%	0%	C	0.105	F	0.512	410	G	2002
						58-756										
						US 58 BUS										
1202	0.13	840	R			58-1205				NA			NA			08/16/2001
						US 58 BUS										
1203	0.29	60	R			58-688				NA			NA			1998
						NCL BOYDTON										
1204	0.11	200	R			58-1205				NA			NA			1998
						SR 92										
1204	0.06	100	R			58-1206				NA			NA			1998
						SR 92										
1204	0.10	60	R			58-1206				NA			NA			1998
						58-1217										
1204	0.10	60	R			58-1217				NA			NA			08/16/2001
						US 58 BUS										
1204	0.12	46	R			ECL BOYDTON				NA			NA			08/16/2001
						58-1206										
1205	0.07	80	R			58-1206				NA			NA			08/16/2001
						58-707										
1205	0.24	150	R			US 58 BUS				NA			NA			1993
						US 58 BUS										
1205	0.08	550	R			58-1204				NA			NA			08/16/2001
						58-1204										

Virginia Department of Transportation  
 Mobility Management Division  
 2002  
 Annual Average Daily Traffic Volume Estimates By Section of Route  
 Town of Boydton

Route	Length	AADT	QA	4Tire	Bus	Truck				QC	Peak Hour	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
<b>Town of Boydton</b>																
1205 58	0.03	20	R			From: 58-1204					NA			NA		08/16/2001
						To: Dead End										
1206 58	0.13	250	R			From: 58-1205					NA			NA		08/16/2001
						To: US 58 BUS										
1206 58	0.08	80	R			From: 58-1204					NA			NA		08/16/2001
						To: 58-1204										
1207 58	0.06	70	R			From: SR 92					NA			NA		08/16/2001
						To: 58-1206										
1208 58	0.06	70	R			From: 58-756					NA			NA		08/16/2001
						To: US 58 BUS										
1209 58	0.19	120	R			From: US 58 BUS					NA			NA		08/16/2001
						To: ECL BOYDTON										
1210 58	0.31	30	R			From: 58-756 EAST					NA			NA		1998
						To: 58-756 WEST										
1211 58	0.10	70	R			From: 58-707					NA			NA		08/16/2001
						To: Dead End										
1213 58	0.03	90	R			From: 58-1214					NA			NA		08/16/2001
						To: 58-756										
1214 58	0.10	60	R			From: Dead End					NA			NA		08/16/2001
						To: 58-1213										
1215 58	0.07	20	R			From: US 58 BUS					NA			NA		08/16/2001
						To: Dead End										
1216 58	0.06	70	R			From: 58-1209					NA			NA		08/16/2001
						To: US 58 BUS										
1217 58	0.13	20	R			From: US 58 BUS					NA			NA		08/16/2001
						To: 58-1204										
1218 58	0.09	40	R			From: 58-1220 WEST					NA			NA		08/16/2001
						To: 58-1220 EAST										
1218 58	0.08	140	R			From: 58-1219					NA			NA		08/16/2001
						To: 58-1219										
1218 58	0.06	210	R			From: 58-707					NA			NA		08/16/2001
						To: 58-707										
1219 58	0.09	48	R			From: 58-1218					NA			NA		08/16/2001
						To: Dead End										
1220 58	0.16	60	R			From: 58-1218 EAST					NA			NA		08/16/2001
						To: 58-1218 WEST										
9253 58	0.05	NA				From: Cul-de-Sac					NA			NA		
						To: 58-1201										