

2011
Virginia Department of Transportation
Daily Traffic Volume Estimates
Including Vehicle Classification Estimates

where available

Special Locality Report

282

Town of Phenix

Information in this report is included in Report

19

(Charlotte County)

Prepared By
Virginia Department of Transportation
Traffic Engineering Division

In Cooperation With
U.S. Department of Transportation
Federal Highway Administration

Virginia Department of Transportation
Traffic Engineering Division
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled “Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes” includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled “Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99”.

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a “Combined Traffic Estimates for Parallel Roadways on this Route” or “Combined Traffic” identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate “NA” for not available.

VDOT’s traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating “NA” for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate “NA” for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems



Interstate Route

Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.



US Route



Virginia State Route



Frontage Road (F precedes frontage route number)



Secondary Route

Special Routes



Bus - Business Route

Bypas - Bypass Route

Truck - Truck Route



ALT - Alternate Route

Wve - Wve Route connector



P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.



The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation
 Traffic Engineering Division
 2011
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Town of Phenix

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	
							2Axle	3+Axle	1Trail	2Trail							
	From:	WCL Phenix															
40 Phenix Main St	Town of Phenix (Maint: 19)	0.97	1000	N	81%	1%	1%	2%	15%	0%	N	0.092	N	0.505	1100	N	
	To:	19-727 Washington Ave; Red House Rd															
	From:	ECL Phenix															
40 Patrick Henry Hwy	Town of Phenix (Maint: 19)	0.62	1900	G	81%	1%	1%	2%	15%	0%	F	0.102	F	0.512	2000	G	
	To:	ECL Phenix															

Virginia Department of Transportation
Traffic Engineering Division
2011
Annual Average Daily Traffic Volume Estimates By Section of Route
Town of Phenix

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
Town of Phenix																
668 19 Stockdale Rd	0.09	50	R								NA			NA		04/06/2009
From: SR 40 Patrick Henry Hwy																
To: 0.09 ME SR 40																
668 19 Stockdale Rd	0.26	20	R								NA			NA		04/20/2006
From: ECL Phenix																
To: SCL Phenix																
675 19 Tola Rd	0.60	410	R								NA			NA		07/17/2000
From: SR 40; 19-1001																
To: SR 40; 19-1008																
727 19 Washington Ave	0.28	1300	G	96%	1%	2%	1%	1%	0%	F	0.149	F	0.542	1300	G	2011
From: NCL Phenix																
To: Dead End																
1001 19 Lincoln St	0.43	80	R								NA			NA		04/08/2009
From: 19-1007 Chester St																
To: SR 40; 19-675																
1001 19 Lincoln St	0.07	210	R								NA			NA		04/08/2009
From: SR 40; 19-675																
To: 19-1005 Park St																
1002 19 Charlotte Ave	0.14	290	R								NA			NA		04/08/2009
From: SR 40 Patrick Henry Hwy																
To: 19-1004 Church St																
1003 19 Virginia Ave	0.07	70	R								NA			NA		04/08/2009
From: 19-1005 Park St																
To: 19-1006 Randolph St																
1003 19 Virginia Ave	0.06	30	R								NA			NA		05/01/2006
From: Dead End																
To: 19-727 Washington Ave; Red House Rd																
1004 19 Church St	0.23	50	R								NA			NA		04/08/2009
From: 19-1003 Virginia Ave																
To: 19-1013 Florida Ave																
1004 19 Church St	0.08	50	R								NA			NA		05/01/2006
From: Dead End																
To: Dead End																
1005 19 Park St	0.09	20	R								NA			NA		04/08/2009
From: 19-1002 Charlotte Ave																
To: 19-727 Washington Ave; Red House Rd																
1005 19 Park St	0.09	47	R								NA			NA		04/08/2009
From: Dead End																
To: Dead End																
1006 19 Randolph St	0.15	50	R								NA			NA		05/01/2006
From: 0.15 ME Dead End																
To: 19-727 Gap																
1006 19 Randolph St	0.21	140	R								NA			NA		05/01/2006
From: Dead End; Gap																
To: 19-1003 Virginia Ave																
1006 19 Randolph St	0.04	20	R								NA			NA		05/01/2006
From: 19-1001 Lincoln St																
To: 19-1008 Chester St																
1007 19 Chester St	0.09	110	R								NA			NA		04/08/2009

Virginia Department of Transportation
 Traffic Engineering Division
 2011
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Town of Phenix

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
Town of Phenix																
1008 19 Chester St	0.07	290	R			From: 19-1007 Chester St						NA		NA		04/08/2009
						To: SR 40; 19-727										
1009 19 Kentucky Ave	0.05	6	R			From: Dead End						NA		NA		05/01/2006
						To: 19-675 Tola Rd										
1010 19 Halifax St	0.05	45	R			From: Dead End						NA		NA		04/08/2009
						To: 0.05 ME Dead End										
1010 19 Halifax St	0.19	60	R			From: 19-727 Red House Rd						NA		NA		05/01/2006
						To: 19-727 Red House Rd										
1011 19 Pennsylvania Ave	0.07	20	R			From: 19-675 Tola Rd						NA		NA		04/08/2009
						To: SR 40 Phenix Main St										
1011 19 Pennsylvania Ave	0.07	40	R			From: 19-1004 Church St						NA		NA		04/08/2009
						To: 19-1004 Church St										
1012 19 Florida Ave	0.05	40	R			From: SR 40 Patrick Henry Hwy						NA		NA		05/01/2006
						To: 19-1013 Florida Ave										
1013 19 Florida Ave	0.06	20	R			From: 19-1012 Florida Ave						NA		NA		05/01/2006
						To: 19-1004 Church St Keysville										
9729 19	0.09	220	R			From: 19-727 Red House Rd						NA		NA		05/01/2006
						To: Phenix Elem School										